



APE Model 150 Vibratory Driver Extractor

The Worlds Largest Provider of
Foundation Construction Equipment



SPECIFICATIONS	DATA
Eccentric Moment	2,200 in-lbs (25.35 kgm)
Drive Force	85 tons (757 kN)
Frequency Maximum (VPM)	0 - 1,650 vpm
Max Line Pull	108 tons (961 kN)
Bare Hammer Weight w/o Clamp	8,330 lbs (3,778 kg)
Throat Width	14.25 in (36 cm)
Length	88.75 in (225 cm)
Height w/o Clamp	72.38 in (184 cm)

APE Model 375 Power Unit

SPECIFICATIONS	DATA
Engine Type	Caterpillar C9 Tier III
Horse Power	375 HP (276 kW)
Drive Pressure	0 - 4,800 psi (331 bar)
Drive Flow	120 gpm (454 lpm)
Clamp Pressure	4,800 psi (69,618 bar)
Clamp Flow	10 gpm (3 lpm)
Engine Speed	2,100 rpm
Weight	12,600 lbs (5,715 kg)
Length	127 in (321 cm)
Width	69 in (174 cm)
Height	82 in (208 cm)
Hydraulic Reservoir	300 gal (1,136 L)
Fuel Capacity	140 gal (530 L)



Specifications may vary due to site conditions, specific hammer conditions or product set up.
Specifications may change without notice.
Consult the factory for details on any specific product (800) 248-8498.



WWW.APEVIBRO.COM
(800) 248-8498
webmaster@apevibro.com

